

TEAKWOOD The Rolls Royce among sunshades

Glatz
Shade in Swiss Quality



Area of use



Type of fastening



Tuscany, Italy



GUSTAV, Zurich



Cafe am Neuen See Berlin

Material and technology

Frame: 8 rods made of teak, continuous pole \varnothing 48 mm, with a double pulley to facilitate easy opening.

Frame material: teak

Frame shape: round or square



Shade cover: with leather reinforcements
material class 5 (100% polyacrylic approx. 300 g/m²)
material class 4 (100% polyester approx. 250 g/m²)

Flounce: not available

Protective cover: included in the standard equipment

Note: The wood is supplied in a natural and therefore untreated state. The wood may secrete colourings and its own natural oils which may leave residues behind on a light coloured cover. This cannot be avoided and is therefore not admissible as a complaint!

Assortment

	Nominal size	Lateral distance	Pole \varnothing	Area covered	Height closed	Clear headroom	Total height	Foundation	Minimum weight for base	max. wind speed open perm.	Order no. Frame teak
	cm	cm	cm	m ²	cm	cm	cm	cm	kg	km/h (wind force)	
	A	AS	M	B	E	F	G	C			
	³ \varnothing 300	275	4.8	6.4	135	220	285	60 × 60	40	30 (5)	166 00 300 731
	³ \varnothing 350	325	4.8	8.7	105	215	285	60 × 60	55	30 (5)	166 00 350 731
	³ 330 × 330	-	4.8	10.9	45	220	285	60 × 60	70	30 (5)	166 00 331 731


³8 parts

The listed measures represent extrapolated average values that may be slightly different on the product ($\pm 2\% \pm 5$ cm).


The height dimensions are based on the ground socket PX. In the base variations these might differ slightly. Apart from the steel base minus 7.5 cm.

The max. wind speed limits as per our separate list apply only in the presence of a fix ground anchorage.


In the presence of several sunshades, the minimum distance between one sunshade and another and between sunshades and walls shall be 20 cm.



Loose cover max. 10 cm, concrete thickness min. 30 cm (pay attention to frost depth), water outflow



8 parts



8 parts

Accessories

	Order no.
Fixing option Z (support tube Z absolutely necessary)	
1. Concrete base Z, 40 kg, \varnothing 60 × 8.5 cm	350 01 109 529
1. Concrete base Z, 55 kg, \varnothing 60 × 11 cm	350 01 109 528
1. Concrete base Z, 70 kg, \varnothing 75 × 9 cm	350 01 109 527
2. Granite base Z 40 kg, \varnothing 53 × 7 cm, natural stone	350 01 109 460
3. ³ Granite base Z, 55 kg, 55 × 55 × 9 cm, natural stone, with castors and retractable handle	350 01 109 440
4. Steel base Z, 40 kg, 58.5 × 58.5 × 2 cm, galvanised steel	350 01 100 210
Add-on weight 30 kg, 57.5 × 57.5 × 1.7 cm, galvanised steel	350 01 100 310
5. Wall bracket Z, 180 mm, galvanised steel	350 01 205 000
6. Support tube Z, \varnothing 48/55 mm, galvanised steel	350 01 201 210
6. Support tube Z, \varnothing 48/55 mm, high-grade steel 1.4301/304	350 01 201 300
Base with castors Z (support tube Z absolutely necessary)	
7. Base with castors Z, 55 kg, 65 × 65 × 11 cm, cast concrete decor	350 01 102 900
7. Base with castors Z, 90 kg, 80 × 80 × 12.5 cm, cast concrete decor	350 01 102 800
Fixing option PX (Connection tube PX absolutely necessary)	
8. Ground socket PX, galvanised steel	350 01 207 001
8. Ground socket PX, high-grade steel 1.4301/304	350 01 207 011
9. Connection tube PX, \varnothing 48/55 mm, galvanised steel	350 01 206 001
9. Connection tube PX, \varnothing 48/55 mm, high-grade steel 1.4301/304	350 01 206 011
Protective cover, coated polyester fabric	
10. Protective cover with zip and rod	350 01 609 969
Miscellaneous items	
11. Rechargeable battery light Osyrion 8 for pole \varnothing 48 – 68 mm, battery charger with european plug (type C) included 1 accumulator included	350 01 557 960
12. Rechargeable battery light Osyrion 6 for pole \varnothing 30 – 50 mm, battery charger with european plug (type C) included 1 accumulator included	350 01 557 950
13. Rechargeable battery light Osyrion 4 for pole \varnothing 30 – 50 mm, battery charger with european plug (type C) included 1 accumulator included	350 01 557 910
Spare accu, 3.7 V, 4800 mAh (for Osyrion 8)	350 01 557 970

³only suitable for smooth, joint free surface coverings

